

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 2 of 35

Alt. Dekt. No.: MP0275 / 13361 045001

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (original) A signal processing apparatus comprising:  
an input to receive a signal;  
a buffer responsive to the input to store the signal;  
a detector responsive to the input to interpret the signal as discrete values; and  
an averaging circuit responsive to the buffer and the detector to cause interpretation, by the detector during a retry mode, of a new signal comprising an average of a previous signal stored in the buffer and a current signal.

2. (currently amended) The apparatus of claim 1, wherein the ~~input~~ signal from the input comprises a read signal received from a storage medium.

3. (currently amended) The apparatus of claim 1, wherein the ~~input~~ signal from the input comprises an analog signal, the

RECEIVED  
APR 11 2006  
FBI

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 3 of 35

Att. Dekt. No.: MP0275 / 13361 045001

apparatus further comprising a filter and an analog to-digital converter (ADC) coupled between the input and the detector.

4. (original) The apparatus of claim 3, wherein the buffer is coupled between the ADC and the filter.

5. (original) The apparatus of claim 3, wherein the buffer is coupled between the filter and the detector.

6. (original) The apparatus of claim 3, wherein the filter comprises a finite impulse response (FIR) digital filter coupled between the ADC and the detector.

7. (original) The apparatus of claim 1, further comprising an error correction circuit responsive to the detector and the averaging circuit to provide a signal quality metric that governs which signals are averaged.

8. (original) The apparatus of claim 1, wherein the detector comprises a Viterbi detector.

9. (original) The apparatus of claim 1, further comprising a control circuit that determines whether the discrete values are adequately indicated based on comparison of

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 4 of 35

Att. Dckt. No.: MP0275 / 13361-045001

interpretations of the new averaged signal and the current signal.

10. (currently amended) The apparatus of claim 1, further comprising a control circuit that causes averaging of a defined number of most recent input signals, wherein the defined number is greater than two.

11. (original) The apparatus of claim 1, further comprising a control circuit that causes the previous signal stored in the buffer to be an averaged input signal when two or more signals are obtained in the retry mode.

12. (original) A storage device, comprising:  
a storage medium;  
a head assembly operable to generate a read signal from the storage medium;  
a buffer that saves the read signal generated by the head assembly;  
a detector that interprets the read signal as discrete values;  
an averaging circuit responsive to the buffer and the detector; and

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 5 of 35

Att. Dekt. No.: MP0275 / 13361-045001

a control circuit responsive to the averaging circuit to cause interpretation by the detector in a retry mode of a new read signal comprising an average of a previous read signal stored in the buffer and a current read signal.

13. (original) The storage device of claim 12, wherein the read signal comprises an analog read signal, the storage device further comprising a filter and an analog-to-digital converter (ADC) coupled between the head assembly and the detector.

14. (original) The storage device of claim 13, wherein the buffer is coupled between the ADC and the filter.

15. (original) The storage device of claim 13, wherein the buffer is coupled between the filter and the detector.

16. (original) The storage device of claim 13, wherein the filter comprises a finite impulse response (FIR) digital filter coupled between the ADC and the detector.

17. (original) The storage device of claim 12, further comprising an error correction circuit responsive to the

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 6 of 35

Att. Dekt. No.: MP0275 / 13361-045001

detector and the averaging circuit to provide a signal quality metric that governs which read signals are averaged.

18. (original) The storage device of claim 17, wherein the detector comprises a Viterbi detector.

19. (original) The storage device of claim 12, wherein the control circuit determines whether the discrete values are adequately indicated based on comparison of interpretations of the new averaged read signal and the current read signal.

20. (currently amended) The storage device of claim 12, wherein the control circuit causes averaging of a defined number of most recent read signals, wherein the defined number is greater than two.

21. (original) The storage device of claim 12, wherein the control circuit causes the previous read signal stored in the buffer to be an averaged read signal when two or more read attempts are made in the retry mode.

22. (currently amended) A method comprising:  
interpreting an input signal as discrete values; and

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 7 of 35

Att. Dckt. No.: MP0275 / 13361-045001

in response to an inadequate signal, averaging multiple signals to improve interpretation of the input signal;

wherein the multiple signals comprise separate signals, representing same data, obtained at different times.

23. (original) The method of claim 22, wherein interpreting the input signal comprises:

sampling the input signal;

storing the sampled input signal; and

detecting the discrete values in the sampled input signal.

24. (original) The method of claim 23, wherein sampling the input signal comprises converting the input signal to a digital signal, storing the sampled input signal comprises storing the digital signal, and the multiple signals to be averaged include the stored digital signal.

25. (original) The method of claim 23, wherein sampling the input signal comprises converting the input signal to a digital signal and filtering the digital signal based on finite impulse response, storing the sampled input signal comprises storing the filtered digital signal, and the multiple signals to be averaged include the stored and filtered digital signal.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 8 of 35

Att. Dekt. No.: MP0275 / 13361-045001

26. (original) The method of claim 22, wherein the input signal comprises a read signal received from a storage medium, interpreting the input signal comprises determining if the read signal adequately indicates the discrete values, and averaging the multiple signals comprises averaging multiple read signals of the storage medium to improve read signal interpretation.

27. (original) The method of claim 22, wherein interpreting the input signal comprises using maximum likelihood detection and error correction to provide the discrete values and a signal quality metric, the method further comprising excluding the input signal from the multiple signals to be averaged based on the signal quality metric.

28. (original) The method of claim 22, wherein averaging the multiple signals comprises:

in response to the input signal inadequately indicating the discrete values, entering a retry mode; and

in the retry mode, obtaining a second signal, averaging the first and second signals, and determining whether the discrete values are adequately indicated based on the averaged signal.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 9 of 35

Att. Dckt. No.: MP0275 / 13361-045001

29. (original) The method of claim 28, wherein determining whether the discrete values are adequately indicated comprises interpreting the averaged signal with a Viterbi detector.

30. (original) The method of claim 28, wherein determining whether the discrete values are adequately indicated comprises comparing interpretations of the averaged signal and of the second signal.

31. (currently amended) The method of claim 28, wherein averaging the multiple signals further comprises, in the retry mode, in response to the discrete values being inadequately indicated, repeatedly obtaining a new signal, averaging most recent signals to generate a newly averaged signal, and determining if the newly averaged signal adequately indicates the discrete values.

32. (original) The method of claim 31, wherein averaging the most recent signals comprises averaging the three most recent signals.

33. (original) The method of claim 28, wherein averaging the multiple signals further comprises, in the retry mode, in



Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 10 of 35

Att. Dckt. No.: MP0275 / 13361-045001

response to the discrete values being inadequately indicated, repeatedly obtaining a new signal, averaging the new signal with the previous averaged signal, and determining if the newly averaged signal adequately indicates the discrete values.

34. (currently amended) A system comprising:

means for storing data; and

means for reading the data, said means for reading

including means for averaging multiple read signals to improve data reading in response to an inadequate read signal;

wherein the multiple signals comprise separate signals, representing same data, obtained at different times.

35. (original) The system of claim 34, wherein the means for storing data comprises magnetic means for storing data.

36. (original) The system of claim 34, wherein the means for averaging comprises means for saving a digital read signal before equalization in a read channel.

37. (original) The system of claim 36, wherein the means for saving a digital read signal comprises means for saving an averaged read signal.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 11 of 35

Att. Dekt. No.: MP0275 / 13361 045001

38. (original) The system of claim 34, wherein the means for reading further includes means for converting the read signals to digital signals, means for filtering the digital signals, and means for detecting stored information in the filtered digital signals.

39. (original) The system of claim 38, wherein the means for averaging comprises means for storing a read signal between the means for converting and the means for filtering.

40. (original) The system of claim 38, wherein the means for averaging comprises means for storing a read signal between the means for filtering and the means for detecting.

41. (original) The system of claim 38, wherein the means for detecting comprises Viterbi means for detecting stored information in the filtered digital signals.

42. (original) The system of claim 34, wherein the means for reading further includes error-detection means for controlling which read signals are averaged.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 12 of 35

Att. Dckt. No.: MP0275 / 13361-045001

43. (original) The system of claim 34, wherein the means for reading further includes means for comparing an averaged read signal and a current read signal.

44. (original) The system of claim 34, wherein the means for averaging comprises means for averaging three or more most recent read signals.

45. (currently amended) An article comprising:  
means for interpreting an input signal as discrete values;  
and  
means for averaging multiple signals, in response to an inadequate signal, to improve interpretation of the input signal;

wherein the multiple signals comprise separate signals, representing same data, obtained at different times.

46. (original) The article of claim 45, wherein the means for interpreting comprises:  
means for sampling the input signal;  
means for storing the sampled input signal; and  
means for detecting the discrete values in the sampled input signal.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 13 of 35

Att. Dckt. No.: MP0275 / 13361-045001

47. (original) The article of claim 46, wherein the means for sampling comprises means for converting the input signal to a digital signal, and the means for storing comprises means for storing the digital signal, and the means for averaging comprises means for averaging the stored digital signal and a current signal.

48. (original) The article of claim 46, wherein the means for sampling comprises means for converting the input signal to a digital signal and means for filtering the digital signal based on finite impulse response, and the means for storing comprises means for storing the filtered digital signal, and the means for averaging comprises means for averaging the stored and filtered digital signal and a current signal.

49. (original) The article of claim 45, wherein the means for interpreting comprises maximum likelihood detection and error correction means for providing the discrete values and a signal quality metric used to exclude an input signal from averaging.

50. (original) The article of claim 45, wherein the means for averaging comprises:

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 14 of 35

Att. Dckt. No.: MP0275 / 13361-045001

means for entering a retry mode in response to the input  
signal inadequately indicating the discrete values;  
means for obtaining a second signal;  
means for averaging the first and second signals; and  
means for determining whether the discrete values are  
adequately indicated based on the averaged signal.

51. (original) The article of claim 50, wherein the means  
for determining comprises Viterbi means for interpreting the  
averaged signal.

52. (original) The article of claim 50, wherein the means  
for determining comprises means for comparing interpretations of  
the averaged signal and of the second signal.

53. (original) An apparatus comprising:  
means for receiving a signal;  
means for storing the signal;  
means for interpreting the signal as discrete values; and  
retry-mode means for interpreting a new signal comprising  
an average of a stored signal and a current signal.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 15 of 35

Att. Dekt. No.: MF0275 / 13361-045001

54. (original) The apparatus of claim 53, wherein the means for receiving comprises means for receiving a read signal from a storage medium.

55. (original) The apparatus of claim 53, further comprising means for converting a received analog signal to a digital signal and means for filtering the digital signal.

56. (original) The apparatus of claim 55, wherein the means for storing comprises means for buffering the digital signal.

57. (original) The apparatus of claim 55, wherein the means for storing comprises means for buffering the filtered digital signal.

58. (original) The apparatus of claim 55, wherein the means for filtering comprises a finite impulse response (FIR) digital filter.

59. (original) The apparatus of claim 53, further comprising means for providing a signal quality metric that governs which signals are averaged.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 16 of 35

Att. Dekt. No.: MF0275 / 13361-045001

60. (original) The apparatus of claim 53, wherein the retry-mode means for interpreting comprises a Viterbi detector.

61. (original) The apparatus of claim 53, further comprising means for determining whether the discrete values are adequately indicated based on comparison of interpretations of the averaged signal and the current signal.

62. (currently amended) The apparatus of claim 53, further comprising means for averaging a defined number of most recent input signals, wherein the defined number is greater than two.

63. (original) The apparatus of claim 53, further comprising means for causing the stored signal to be an averaged input signal when two or more signals are obtained in a retry mode.

64. (currently amended) A machine-readable medium embodying information indicative of instructions for causing one or more machines to perform operations comprising:

interpreting an input signal as discrete values; and

in response to an inadequate signal, averaging multiple signals to improve interpretation of the input signal;

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 17 of 35

Att. Dekt. No.: MP0275 / 13361-045001

whercin the multiple signals comprise separate signals,  
representing same data, obtained at different times.

65. (original) The machine-readable medium of claim 64,  
wherein interpreting the input signal comprises:  
sampling the input signal;  
storing the sampled input signal; and  
detecting the discrete values in the sampled input signal.

66. (original) The machine-readable medium of claim 65,  
wherein sampling the input signal comprises converting the input  
signal to a digital signal, storing the sampled input signal  
comprises storing the digital signal, and the multiple signals  
to be averaged include the stored digital signal.

67. (original) The machine-readable medium of claim 65,  
wherein sampling the input signal comprises converting the input  
signal to a digital signal and filtering the digital signal  
based on finite impulse response, storing the sampled input  
signal comprises storing the filtered digital signal, and the  
multiple signals to be averaged include the stored and filtered  
digital signal.



Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 18 of 35

Att. Dckt. No.: MP0275 / 13361-045001

68. (original) The machine-readable medium of claim 64, wherein the input signal comprises a read signal received from a storage medium, interpreting the input signal comprises determining if the read signal adequately indicates the discrete values, and averaging the multiple signals comprises averaging multiple read signals of the storage medium to improve read signal interpretation.

69. (original) The machine-readable medium of claim 64, wherein interpreting the input signal comprises using maximum likelihood detection and error correction to provide the discrete values and a signal quality metric, and the operations further comprise excluding the input signal from the multiple signals to be averaged based on the signal quality metric.

70. (original) The machine-readable medium of claim 64, wherein averaging the multiple signals comprises:

in response to the input signal inadequately indicating the discrete values, entering a retry mode; and

in the retry mode, obtaining a second signal, averaging the first and second signals, and determining whether the discrete values are adequately indicated based on the averaged signal.

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 19 of 35

Att. Dckt. No.: MP0275 / 13361-045001

71. (original) The machine-readable medium of claim 70, wherein determining whether the discrete values are adequately indicated comprises interpreting the averaged signal with a Viterbi detector.

72. (original) The machine-readable medium of claim 70, wherein determining whether the discrete values are adequately indicated comprises comparing interpretations of the averaged signal and of the second signal.

73. (original) The machine-readable medium of claim 70, wherein averaging the multiple signals further comprises, in the retry mode, in response to the discrete values being inadequately indicated, repeatedly obtaining a new signal, averaging most recent signals, and determining if the newly averaged signal adequately indicates the discrete values.

74. (original) The machine-readable medium of claim 73, wherein averaging the most recent signals comprises averaging the three most recent signals.

75. (original) The machine-readable medium of claim 70, wherein averaging the multiple signals further comprises, in the

Applicant : Hongxin Song et al.  
Serial No.: 10/600,419  
Filed: June 20, 2003  
Page : 20 of 35

Att. Dckt. No.: MP0275 / 13361-045001

retry mode, in response to the discrete values being  
inadequately indicated, repeatedly obtaining a new signal,  
averaging the new signal with the previous averaged signal, and  
determining if the newly averaged signal adequately indicates  
the discrete values.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**